



Technical data

Power: 10kw
 Size (mm): B400 / D380 / H700
 Weight: 28kg
 Supply: 400V / 50Hz, 20A


Performance features

- compact table-top device
- max. chuck length: 300mm
- Ø 3-32 (HM shank)
- Ø 6-32 (HSS shank)

Induction shrinking device for the fixing of HM and HSS tools

With this redesign, well-proved components were partly taken over from predecessor models and summarized. In particular firm places were created for the accessories, e.g. shrinking aids etc. so that in the working area of the device, order and handiness have a high significance.

With this device both HM tools (of Ø3 - Ø32) as also steel in steel (of Ø6 - Ø32) can be shrunk. The corresponding parameters for time and performance are set aside in an internal database. This makes an overheating situation virtually impossible for a skilled operator.



Quick-change adapter sockets

HSK-A80	Order no.	990-356
HSK-A/E63		990-354
HSK-A/E50		990-353
HSK-A/E40		990-352
HSK-A/E32		990-351
HSK-E25		990-350
SK40/BT40		990-354
SK30/BT30		990-355
PSC63		990-354
others on request		

Screening rings



Ø3 - Ø5	Art.-Nr.	990-605
Ø6 - Ø12	Art.-Nr.	990-612
Ø14 - Ø16	Art.-Nr.	990-616
Ø18 - Ø20	Art.-Nr.	990-620
Ø25 - Ø32	Art.-Nr.	990-632

Protection gloves Art.-No.: 990-398



Universal shrinking aid Art.-No.: 990-399

Art.-No.: 990-011CS