



► 4 břité závitové frézy pro **G a Rp** závity



Použití pro
VNITŘNÍ
i **VNĚJŠÍ**
závity



OCELI ≤ 62 HRC - NEREZ - TITAN

| G / Rp | Sklad | Stoupání TPI | G | | Rp | | D (mm) | L2 (mm) | L (mm) | d h5 (mm) | Standardní položka | | |
|----------------------|-------|-----------------|--------------|------|--------------|------|-----------|------------|-----------|--------------|-------------------------------------|-------------|-------|
| | | | PRO ZÁVIT | | PRO ZÁVIT | | | | | | | | |
| 4BSP-060-095-S06-G28 | ● | 28 | G 1/16" | 6,7 | Rp 1/8" | 8,6 | 6 | 9,5 | 60 | 6 | <input checked="" type="checkbox"/> | | |
| | | | G 1/8" | 8,7 | | | | | | | | | |
| 4BSP-080-140-S08-G19 | ● | 19 | G 1/4" | 11,7 | Rp 1/4" | 11,4 | 8 | 14 | 65 | 8 | <input checked="" type="checkbox"/> | | |
| | | | G 3/8" | 15,2 | | | | | | | | Rp 3/8" | 14,9 |
| 4BSP-120-265-S12-G14 | ● | 14 | G 1/2" | 18,9 | Rp 1/2" | 18,6 | 12 | 26,5 | 80 | 12 | <input checked="" type="checkbox"/> | | |
| | | | G 5/8" | 20,9 | | | | | | | | | |
| | | | G 3/4" | 24,4 | | | | | | | | Rp 3/4" | 24,1 |
| 4BSP-160-380-S16-G11 | ● | 11 | G 1" | 30,6 | Rp 1" | 30,3 | 16 | 38 | 105 | 16 | <input checked="" type="checkbox"/> | | |
| | | | G 1 - 1/8" | 35,3 | | | | | | | | | |
| | | | G 1 - 1/4" | 39,3 | | | | | | | | Rp 1 - 1/4" | 38,95 |
| | | | G 1 - 1/2" | 45,2 | | | | | | | | Rp 1 - 1/2" | 44,85 |
| | | | G 1 - 3/4" | 51 | | | | | | | | Rp 2" | 56,6 |
| G 2" | 57 | | | | | | | | | | | | |

● - skladová položka

Pokud potřebuje **delší odlehčení L2**, dejte nám prosím vědět, posoudíme možnosti.



NÁŠ TIP:


dodáváme také široký sortiment závitových kalibrů na závity G, Rp, Rc a R:

G



www.pm-tech.cz/kalibry-g

Rp - Rc - R



www.pm-tech.cz/kalibry-r