



# ► 4 břitové závitové frézy pro M závity



Použití pro  
**VNITŘNÍ**  
závit




**NÁŠ TIP:**

Tyto záv. frézy lze použít i pro:

- **MJ** závity (letecký průmysl)
- **EG-M** závity (závitové vložky)

**OCELI ≤ 62 HRC - NEREZ - TITAN**

Objednací číslo	Sklad	Stoupání P (mm)	M		L2 (mm)	D (mm)	L (mm)	d h5 (mm)	Standardní položka
			PRO ZÁVIT						
4STM-024-075-S06-M3	●	0,5	<b>M3</b>	2,5	<b>7,5</b>	2,4	50	6	<input checked="" type="checkbox"/>
4STM-031-100-S06-M4	●	0,7	<b>M4</b>	3,3	<b>10</b>	3,1	50	6	<input checked="" type="checkbox"/>
4STM-038-125-S06-M5	●	0,8	<b>M5</b>	4,2	<b>12,5</b>	3,8	50	6	<input checked="" type="checkbox"/>
4STM-046-150-S06-M6	●	1	<b>M6</b>	5	<b>15</b>	4,6	50	6	<input checked="" type="checkbox"/>
4STM-062-200-S10-M8	●	1,25	<b>M8</b>	6,8	<b>20</b>	6,2	70	10	<input checked="" type="checkbox"/>
4STM-075-250-S10-M10	●	1,5	<b>M10</b>	8,5	<b>25</b>	7,5	70	10	<input checked="" type="checkbox"/>
4STM-090-300-S10-M12	●	1,75	<b>M12</b>	10,2	<b>30</b>	9	80	10	<input checked="" type="checkbox"/>
4STM-115-400-S12-M16	●	2	<b>M16</b>	14	<b>40</b>	11,5	100	12	<input checked="" type="checkbox"/>
4STM-140-450-S16-M18	●	2,5	<b>M18</b>	15,5	<b>45</b>	14	135	16	<input checked="" type="checkbox"/>
4STM-150-500-S16-M20	●	2,5	<b>M20</b>	17,5	<b>50</b>	15	135	16	<input checked="" type="checkbox"/>

● - skladová položka

Pokud potřebuje **delší odlehčení L2**, dejte nám prosím vědět, posoudíme možnosti.



**NÁŠ TIP:**

dodáváme také široký sortiment závitových kalibrů na metrické závity:



[www.pm-tech.cz/kalibry-m](http://www.pm-tech.cz/kalibry-m)

